



## HIS InterSecure Solutions (S) Pte Ltd

Blk 1092 Lower Delta Road #04-06/07  
Tiong Bahru Industrial Estate. Singapore 169203  
Tel: (65) 62727375, Fax: (65) 62733073  
Website: [www.hiss.com.sg](http://www.hiss.com.sg)

### LORD DUCHESS SAFE

#### **BODY**

The LORD DUCHESS SAFE body incorporates the LORD special designed barrier encased within the steel walls protecting all five sides of the safe body with a single case unit of consistent strength, free of surface seams thus gives the safe body its immense strength and protective qualities, offering great resistance to attack



#### **DOOR**

The door incorporates the LORD special designed barrier encased between heavy steel press formed plates with the lockcase forming an integral part of the door structure. Further, additional security has been achieved from a unique method of anchoring the LORD AP Bar material to eliminate the removal by attackers of the outer door steel.

#### **BOLTWORK**

A series of heavy-duty 20mm running bolts secure the safe door in special reinforced sections within the safe body. Long throw bolts lock directly into the recess of the body (in cup form) for uniform strength between the door & body. Even when the hinges are cut off, the door remains securely locked into the body.

#### **LOCKING**

The locking mechanism is controlled by one keylock and one 3-wheel combination lock the numbers of which is changeable at will by the user. The combination lock is easy to operate and is capable of one million-code change.

#### **RATED BY EUROPEAN SAFE RATING COMMITTEE**

The LORD DUCHESS SAFE is one of the few small safes rated by the European Safe Rating Committee under Class 7 for burglary protection. The recommended insurance coverage is £6000 British Pounds.



#### **INTERNATIONAL RATING & TESTING STANDARDS**

Lord Safes are manufactured to well known standards which include the UL standard (Underwriters' Laboratories Incorporation Std USA), SIRIM Standard (for hydraulic Jack Attack) JIS Standard (Japanese Industrial Std) & VDMA (German Standard).

#### **DIMENSIONS**

Weight	EXTERNAL			INTERNAL		
	H	W	D	H	W	D
Kg (approx)						
91kg	370mm	450mm	410mm	245mm	365mm	280mm